

D-Lox® post

Post system for flat panels. Two fixings systems are available: with clamps or with U-cover plate.





Benefits

- Two fixing systems available
- Panel-mounting support pre-installed on post

Profile

- Welded rectangular posts
- Cross section of the post: 60 x 40mm
- Plate thickness: 1.5 or 2mm depending on post height
- Plastic cap pre-mounted on the post
- I/V: 5.00 cm³ (for plate thickness: 1.5mm) or I/V: 6.19cm³ (for plate thickness:
- M8 inserts pre-installed

Accessories/options

- Metal panel fixators
- U-cover plates
- Separate slide-in foot plate or welded foot plate
- Security bolts M8 x 40

(minimum 60 microns).

Colours

Coating technique

- Bent arms
- Corner clamps

Product detail



With cover plate



Green RAL 6005 and Anthracite RAL 7016. Hot-dip galvanised finish available. Other colours are available on request.



Com	natihla	products
OUITI	patible	products

- Nylofor® 2D
- Nylofor® 2DS
- Nylofor® F

Panel height (mm)	Post section (mm)	Post length (mm)	Number of clamps per post
630	60 x 40 x 1.5	1000	3
830	60 x 40 x 1.5	1300	3
1030	60 x 40 x 1.5	1500	4
1230	60 x 40 x 1.5	1700	4
1430	60 x 40 x 1.5	2000	4
1630	60 x 40 x 1.5	2200	5
1830	60 x 40 x 2	2400	5
2030	60 x 40 x 2	2600	5
2230	60 x 40 x 2	3000	6
2430	60 x 40 x 2	3200	6

Galvanised inside and outside (275g/m² - both sides combined) and plastic coated

Europe: Blokkestraat 34b, B-8550 Zwevegem Tel: B: +32 56 73 46 46

USA: 3309 SW Interstate 45, Ennis, TX 75119 Tel: +1 972 878 7000

Middle East: P.O. Box 293517 DAFZA, Building E 5, Block A 8th Floor, Office 802 Tel: +971 04 6091122 Africa: B10, Bergriver Business Park, Paarl, 7646 Tel: +27 021 868 7300

