

E-Lox® post

Posts for Nylofor F and all Nylofor 3D panelsystems. A flexible post distance results in a simple and economical installation.





Benefits

- "Endless" installation
- Panels can be installed following the slope

Profile

- Welded rectangular posts
- Cross section of the post: 60 x 40 x 2.0mm
- Plastic cap pre-mounted on the post
- I/V: 6.19cm³
- Pre-drilled holes for fixing the corresponding hook screws in M8 with break-off nut

Accessories/options

- Separate slide-in foot plate or welded foot plate
- Bent arms (single or double sided)
- Hooks M8 x 80 for Nylofor 3D panels and specific panels connector
- Hooks M8 x 90 for Nylofor F panels and specific panels connector
- Angles and slopes connectors

Coating technique



Galvanised inside and outside (275g/m² – both sides combined) and plastic coated (minimum 60 microns).

Colours

Green RAL 6005 and Anthracite RAL 7016. Hot-dip galvanised finish available. Other colours are available on request.

Product detail



E-Lox [®] post range			
Panel height (mm)	Post section (mm)	Post length (mm)	Number of hooks per post
630	60 x 40 x 2	1000	2
830	60 x 40 x 2	1300	2
1030	60 x 40 x 2	1500	3
1230	60 x 40 x 2	1700	3
1430/1530	60 x 40 x 2	2000	4
1630/1730	60 x 40 x 2	2200	4
1830	60 x 40 x 2	2400	4
2030	60 x 40 x 2	2600	5
2230	60 x 40 x 2	3000	6
2430	60 x 40 x 2	3200	6

Compatible products

- Nylofor® 3D (XL)
- Nylofor® 3D+
- Nylofor® 3D Essential
- Nylofor® 3D Light
- Nylofor® F

Europe: Blokkestraat 34b, B-8550 Zwevegem Tel: B: +32 56 73 46 46

USA: 3309 SW Interstate 45, Ennis, TX 75119 Tel: +1 972 878 7000 Middle East: P.O. Box 293517 DAFZA, Building E 5, Block A 8th Floor, Office 802 Tel: +971 04 6091122 **Africa:** B10, Bergriver Business Park, Paarl, 7646 Tel: +27 021 868 7300

