

Izifix® post

Profiled post, without fixators, compatible with 3D and 2D panels types. Easy and fast to install. Ideal for fence erectors looking for reliability and cost-efficiency.



Benefits

- No fixators needed to maintain panels
- Long linguets for efficient stability of the panel into the post
- Angles up to 180° with the same post
- Slope installation with 100mm steps
- No need to cut 3D profile to install the panel
- Cost-effective system

Profile

- Dimensions: 75 x 50mm
- Slot every 100mm
- Slope installation: 100mm steps
- Yield strength: minimum 250MPa
- Betafence branding on the front of the post
- Supplied with plastic cap

Accessories/options

- Tensioning tool to ensure a correct and easy installation
- Separate slide-in base plate

Coating technique



Galvanised inside and outside (275g/m² – both sides combined) and polyester plastic coated (minimum 60 microns).

Colours

Green RAL 6005, White RAL 9010, Black RAL 9005 and Anthracite RAL 7016. Other colours are available on request.

Product detail



Compatible products

- Nylofor® 3D (XL)
- Nylofor® 3D+
- Nylofor® 3D Essential
- Nylofor® 3D Light
- Nylofor® 2D*
- Nylofor® 2DS*
- Bekafor® Classic

Izifix® post range		
Post length (mm)	Fence height (mm) on base plate	Fence height (mm) in concrete
1075	1030	630
1275	1230	830
1475	-	1030
1575	1530	-
1775	1730	-
1975	1930	1530
2175	-	1730
2475	2430*	1930
2575	-	2030

* Not compatible for Nylofor 2D and 2DS panels

Europe: Blokkestraat 34b,
B-8550 Zwevegem
Tel: B: +32 56 73 46 46

USA: 3309 SW Interstate 45,
Ennis, TX 75119
Tel: +1 972 878 7000

Middle East: P.O. Box 293517 DAFZA,
Building E 5, Block A 8th Floor, Office 802
Tel: +971 04 6091122

Africa: B10, Bergriver Business Park,
Paarl, 7646
Tel: +27 021 868 7300