Nylofor® Twilfix post

Square posts, polyester coated on galvanised with a special fixing system. To be used with all Nylofor panels.





Benefits

- Universal post designed to fit all our low to medium security panels
- Classic square design
- Posts include stepping holes for installations on sloped ground; extra holes provide 100mm option

Profile

- Tubular post with square cross section 60 x 60 x 1.5mm
- M8 inserts and fixators for the fixation to the front of the post
- Standard plastic post cap with the Betafence logo
- Separate slide-in base plates available or welded plates possible on request
- I/V: 6.68cm³

Accessories/options

- Polyamide fixators
- Stainless steel bolts
- Bent arm
- Base plate
- Concrete plate holder
- Corner clamps

Coating technique



Galvanised inside and outside (275g/m² – both sides combined) and polyester plastic coated (minimum 60 microns).

Colours

Green RAL 6005, Black RAL 9005, White RAL 9010 and Anthracite RAL 7016. Other colours are available on request.

Product detail



Compatible products

- All Nylofor® panels
- Screeno® Line Privacy

For more information please visit praesidiad.com

Collfort® Privacy

Nylofor® Twilfix post range				
Fence height (mm)	Post for concrete height (mm)	Post with base plate height(mm)	Number of fixators per intermediate and end post	Number of fixators per comer post
630	1000	674	3	6
1030	1500	1074	3	6
1230	1800	1274	4	8
1430	2100	1474	4	8
1530	2100	1574	4	8
1630	2400	1674	5	10
1730	2400	1774	5	10
1830	2500	1874	5	10
1930	2500	1974	5	10
2030	2700	2074	6	12
2230	-	2274	6	12
2430	3100/3400	2474	7	14

Europe: Blokkestraat 34b, B-8550 Zwevegem Tel: B: +32 56 73 46 46

USA: 3309 SW Interstate 45, Ennis, TX 75119 Tel: +1 972 878 7000 Middle East: P.O. Box 293517 DAFZA, Building E 5, Block A 8th Floor, Office 802 Tel: +971 04 6091122 **Africa:** B10, Bergriver Business Park, Paarl, 7646 Tel: +27 021 868 7300

