

O-Lox® post

Rigid post system with cover plate or stainless steel fixing plate. Variable fixing systems and post caps.





Benefits

- Three different fixing systems for one standard post
- Possibility to choose the post cap
- Steps of 200mm


Profile

- Posts are built with M8 inserts every 200-400mm
- PA clamps to support the panels are fixed to the posts into inserts
- Cross section post: 60 x 40mm
- Plate thickness: 1.50mm or 2mm, depending on the height of the fence
- I/V 1.5mm = 5.0cm³
- I/V 2.0mm = 6.19cm³
- Post cap with overhang when combined with coverplate or without overhang when combined with butterfly or metal plate

Accessories/options

- Stainless steel butterfly fixators
- Full-length metal cover plate, coated same colour as the post, 40 x 4mm
- Corner clamps
- Stainless steel fixing plates
- Separate slide-in foot plate or welded foot plate

Product detail



With cover plate







With metal plate

Coating technique



Galvanised inside and outside (275 g/m² – both sides combined) and plastic coated (minimum 60 microns).

Colours

Green RAL 6005 and Anthracite RAL 7016. Hot-dip galvanised finish available. Other colours are available on request.

O-Lox [⊚] post range			
Panel height (mm)	Post section (mm)	Post length (mm)	Inserts
630	60 x 40 x 1.5	1000	3
830	60 x 40 x 1.5	1300	4
1030	60 x 40 x 1.5	1500	4
1230	60 x 40 x 1.5	1700	5
1430	60 x 40 x 1.5	2000	5
1630	60 x 40 x 1.5	2200	6
1830	60 x 40 x 2	2400	6
2030	60 x 40 x 2	2600	7
2230	60 x 40 x 2	2800	7
2430	60 x 40 x 2	3000	8

Compatible products

- Nylofor® 2D
- Nylofor® 2DS

Europe: Blokkestraat 34b, B-8550 Zwevegem Tel: B: +32 56 73 46 46

USA: 3309 SW Interstate 45, Ennis, TX 75119 Tel: +1 972 878 7000

Middle East: P.O. Box 293517 DAFZA, Building E 5, Block A 8th Floor, Office 802 Tel: +971 04 6091122

Africa: B10, Bergriver Business Park, Paarl, 7646 Tel: +27 021 868 7300

