O-Lox[®] Super post

Rigid post system with cover plate or stainless steel fixing plate to combine with privacy strips.





Benefits

- Strong and rigid post system for combination with Screeno Wave privacy strips
- Post profile suitable for fence heights up to 4m
- Steps of 200mm are possible

Profile

- Posts are foreseen of inserts every 200-400mm
- PA clamps to support the panels are fixed to the posts with inserts M8
- Cross section post: 120 x 40mm
- Plate thickness: 2mm, depending on the height of the fence
- I/V: 17.34 cm³
- Plastic cap on top of the post

Accessories/options

- Flat steel cover plates (40 x 4mm)
- Stainless steel butterfly fixator
- Corner clamps
- Foot plate
- Base plate holder

Coating technique




Galvanised inside and outside (275g/m² – both sides combined) and polyester plastic coated (minimum 60 microns). Hot-dip galvanised execution is available on resquest.

Colours

Green RAL 6005 and Anthracite RAL 7016. Other colours are available on request.

Product detail



O-Lox [®] Super post (panels with privacy infill in concrete) range						
Panel height (mm)	Post section (mm)	Post length (mm)	Inserts			
1830	120 x 40 x 2	2400	6			
2030	120 x 40 x 2	2700	7			

O-Lox [®] Super post (panels with privacy infill on foot plate) range					
Panel height (mm)	Post section (mm)	Post length (mm)	Inserts		
1830	120 x 40 x 2	1884	6		
2030	120 x 40 x 2	2084	7		

O-Lox [®] Super post (panels not filled) range					
Panel height (mm)	Post section (mm)	Post length (mm)	Inserts		
3060 (1030 + 2030)	120 x 40 x 2	3800	11		
4060 (2030 + 2030)	120 x 40 x 2	4800	14		

Compatible products

- Nylofor® 2D
- Nylofor® 2DS
- Screeno® Wave Privacy

Europe: Blokkestraat 34b, B-8550 Zwevegem Tel: B: +32 56 73 46 46

USA: 3309 SW Interstate 45, Ennis, TX 75119 Tel: +1 972 878 7000 Middle East: P.O. Box 293517 DAFZA, Building E 5, Block A 8th Floor, Office 802 Tel: +971 04 6091122 **Africa:** B10, Bergriver Business Park, Paarl, 7646
Tel: +27 021 868 7300

