Securifor® rectangular post

Rectangular posts, polyester coated on galvanised plate with special fixing system.





Benefits

 Frontal fixation of Securifor panels on Securifor square posts by means of special fixing brackets or clamp bars

Profile

- Posts made of galvanised steel profiles
- Intermediate and end posts: 80 x 60 x 2.5mm or 120 x 60 x 3.0mm with inserts for frontal fixation of panels
- Corner posts: 80 x 60 x 2.5mm or 120 x 60 x 3mm with one insert on two adjacent sides to insert two panels in an angle
- I/V: 15.1cm³ (80 x 60 x 2.5mm)
- I/V: 31.98cm³ (120 x 60 x 3mm)

Fixing methods

- Spider fixator
- Flat steel cover plate 30 x 5mm
- Flat steel cover plate 60 x 6mm

Options

- Posts with welded base plate
- Single, double-welded or bolted vertical extension arms to support three rows of barbed wire available to provide additional security
- Other non-standard post lengths and/or sections are available on request

Coating technique



Galvanised inside and outside (275g/ m^2 – both sides combined) and polyester plastic coated (minimum 60 microns).


Colours

Green RAL 6005. Other colours are available on request.

Securifor [®] rectangular post range				
Panel height (mm)	Securifor post with flat cover plate 60 x 6 (mm)	Securifor post with spider fixator (mm)	Securifor B-Thru post (mm)	Post length (mm)
2000		80 x 60 x 2.5		2600
2400		80 x 60 x 2.5		3100
3000		80 x 60 x 2.5		3700
4000	120 x 60 x 3.0		=	4800

Product detail





Compatible products

- Securifor® Flat
- Securifor® 2D
- Securifor® 3D (only with spiders)
- Securifor® 4D

Europe: Blokkestraat 34b, B-8550 Zwevegem Tel: B: +32 56 73 46 46 **USA:** 3309 SW Interstate 45, Ennis, TX 75119 Tel: +1 972 878 7000 Middle East: P.O. Box 293517 DAFZA, Building E 5, Block A 8th Floor, Office 802 Tel: +971 04 6001122 **Africa:** B10, Bergriver Business Park, Paarl, 7646 Tel: +27 021 868 7300

